

WHIRLPOOL

REFRIGERATION

04/2012



www.whirlpool-professional.com


SENSING THE DIFFERENCE

The Whirlpool professional range of cooling appliances addresses the needs of small and large operators alike.

Tables, cabinets, ice makers, shock freezers and cold rooms in the Whirlpool professional range feature the most advanced technology in the industry.

HIGH FLEXIBILITY

The variety of models, sizes, functions and technologies is capable of meeting every need and guaranteeing perfect results.

SUPERIOR QUALITY

Built to last, with a reliable structure and high-quality components.


















SAVINGS

With our latest generation of cooling products, we paid close attention to energy saving, ecology, easy maintenance and, of course, operator safety.

The range consists of:

- Support refrigerators and freezers
- Glass Door refrigerators
- Professional cabinets and tables
- Ice makers
- Shock freezers



	silver		number of doors		gas		external dimensions mm WxDxH
	white		temperature range °C		electrical connection rating kW		kg ice production in 24 hours
	gross capacity lt		number of grid supports		voltage V		kg ice storage capacity
	number of cells		number of grids included		power hp		grid dimensions mm WxD
	Max productivity per cycle/kg						

SUPPORT CABINETS

REFRIGERATORS

ACO 050 - ACO 051 - ACO 052 - ACO 053



- Certified for commercial use
- Optimum performance-to-price ratio
- Low noise level
- Patented smooth opening system
- Electronic control type with 6th Sense Technology
- Digital display
- Intelligent defrost
- Ventilated
- New antibacterial filter
- Automatic water evaporation system
- High-efficiency compressor
- R600a gas type
- HCFC and CFC free
- Robust handle
- Pigeon pair with the freezer
- Reversible door
- Adjustable feet
- Grid dimensions 400x510 mm
- Perfect for kiosks, pubs, small restaurants, B&Bs

CODE	Colour	lt									
ACO 050		376	1	1	+3°C +7°C	7	7	R600a	0,15	230V~50 Hz	625x596x1790
ACO 051		376	1	1	+3°C +7°C	7	7	R600a	0,15	230V~50 Hz	625x596x1790
ACO 052		325	1	1	+3°C +7°C	6	5 + 1 glass shelf	R600a	0,15	230V~50 Hz	625x596x1590
ACO 053		325	1	1	+3°C +7°C	6	5 + 1 glass shelf	R600a	0,15	230V~50 Hz	625x596x1590

FREEZERS

ACO 054 - ACO 055 - ACO 056 - ACO 057



- Certified for commercial use
- Optimum performance-to-price ratio
- Low noise level
- Patented smooth opening system
- Electronic control type with 6th Sense Technology
- Digital display
- High-efficiency compressor
- R600a gas type
- HCFC and CFC free
- Robust handle
- Pigeon pair with the refrigerators
- Reversible door
- Adjustable feet
- Perfect for kiosks, pubs, small restaurants, B&Bs

CODE	Colour	lt									
ACO 054		266	1	1	-24°C -16°C	7 shelved static evaporator (5 drawers + 2 flap)	-	R600a	0,10	230 V~50 Hz	625x596x1790
ACO 055		266	1	1	-24°C -16°C	7 shelved static evaporator	-	R600a	0,10	230 V~50 Hz	625x596x1790
ACO 056		232	1	1	-24°C -16°C	6 shelved static evaporator (4 drawers + 2 flap)	-	R600a	0,08	230 V~50 Hz	625x596x1590
ACO 057		232	1	1	-24°C -16°C	6 shelved static evaporator	-	R600a	0,08	230 V~50 Hz	625x596x1590

SUPPORT CABINETS TRADITIONAL LINE

REFRIGERATORS

ACO 032/1 - ACO 033/1 - ACO 038/1 - ACO 039/1



- Certified for commercial use
- Electronic control type
- Digital display
- Automatic defrost
- Ventilated
- Automatic water evaporation system
- R134a gas type
- HCFC and CFC free
- Pigeon pair with the freezer
- Reversible door (with a kit for 640 lt)
- Adjustable feet
- Door lock
- Stainless Steel sheet scotchbrite - AISI 430 anti touch treatment for Silver version
- Grid dimensions 515x400 mm (380 lt)
- Grid dimensions GN 1/1 (640 lt)

For accessories please refer to page 7













CODE	Colour	lt									
ACO 032/1		380	1	1	0°C +8°C	5	5	R134a	0,16	230V ~50 Hz	600x610x1865
ACO 033/1		380	1	1	0°C +8°C	5	5	R134a	0,27	230V ~50 Hz	600x610x1865
ACO 038/1		640	1	1	0°C +8°C	5	5	R134a	0,27	230V ~50Hz	775x730x1865
ACO 039/1		640	1	1	0°C +8°C	5	5	R134a	0,27	230V ~50Hz	775x730x1865

FREEZERS

ACO 034/1 - ACO 035/1 - ACO 036/1 - ACO 037/1



- Certified for commercial use
- Electronic control type
- Digital display
- R404a gas type
- HCFC and CFC free
- Pigeon pair with the refrigerators
- Reversible door (with a kit for 640 lt)
- Adjustable feet
- Door lock
- Stainless Steel sheet scotchbrite - AISI 430 anti touch treatment for Silver version

CODE	Colour	lt									
ACO 034/1		380	1	1	-18°C -25°C	6 shelved static evaporator	-	R404a	0,19	230V~50 Hz	600x610x1865
ACO 035/1		380	1	1	-18°C -25°C	6 shelved static evaporator	-	R404a	0,19	230V~50 Hz	600x610x1865
ACO 036/1		640	1	1	-18°C -25°C	6 shelved static evaporator	-	R404a	0,36	230V~50 Hz	775x730x1865
ACO 037/1		640	1	1	-18°C -25°C	6 shelved static evaporator	-	R404a	0,36	230V~50 Hz	775x730x1865

Accessories support cabinets Traditional line
















AGS 393		wheel kit 380 lt
ADN 285		wheel kit 640 lt
AGS 394		4 feet kit 150 mm 380 lt
AGS 395		4 feet kit 150 mm 640 lt
AGS 391		plastic coated grid 515x400 mm for 380 lt
AGS 392		plastic coated grid GN 1/1 for 640 lt

GLASS DOOR REFRIGERATORS

ADN 200/1 - ADN 201/1 - ADN 202/1 - ADN 203/1 - ADN 230/1 - ADN 221



- Certified for commercial use
- Optimum performance-to-price ratio
- Mechanical control
- Automatic defrost
- Ventilated
- LED internal light
- Automatic water evaporation system
- R600a gas type
- HCFC and CFC free
- Robust handle
- Reversible door
- Door lock
- Adjustable feet
- ADN 202/1, ADN 203/1, ADN 230/1 with analog thermometer
- Grid dimensions 525x360 mm (except for ADN221)
- Grid dimensions 488x490 mm only for ADN221
- Perfect for kiosks, pubs, small restaurants

CODE	Colour	lt									
ADN 200/1		290	1	1	0°C +10°C	10	5	R600a	0,20	230 V~50 Hz	600x600x1450
ADN 201/1		350	1	1	0°C +10°C	12	6	R600a	0,23	230 V~50 Hz	600x600x1730
ADN 202/1		290	1	1	0°C +10°C	10	5	R600a	0,20	230 V~50 Hz	600x600x1450
ADN 203/1		350	1	1	0°C +10°C	12	6	R600a	0,23	230 V~50 Hz	600x600x1730
ADN 230/1		350	1	2	0°C +10°C	12	6	R600a	0,23	230 V~50 Hz	600x600x1730
ADN 221		480	1	1	+2°C +14°C	-	5	R600a	0,25	230 V~50 Hz	600x685x2025

ADN 213
ADN 214

ADN 215

ADN 216
ADN 225



- AISI 304 Stainless Steel both internally and externally
- Electronic control type
- Digital display
- Automatic defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Products with solid door are tropicalised (43°C max ambient temperature)
- Products with glass door 25°C max ambient temperature
- Reversible door
- Adjustable plastic feet
- Door lock
- Internal light
- Evaporator inside the cell
- Stainless Steel grid supports
- Plastic coated grids GN 2/1

For accessories please refer to page 12

REFRIGERATORS

CODE	lt									
ADN 213	700	1	1	-2°C +8°C	23	3	R404a	0,34	230 V~50 Hz	720x860x2020
ADN 215	700	1	1	+1°C +10°C	23	3	R404a	0,35	230 V~50 Hz	720x860x2020
ADN 225	700	2	2	+1°C +10°C	23	4	R404a	0,68	230 V~50 Hz	720x860x2020

FREEZERS

CODE	lt									
ADN 214	700	1	1	-18°C -20°C	23	3	R404a	0,54	230 V~50 Hz	720x860x2020

COMBI

CODE	lt									
ADN 216	700	2	2	-2°C +8°C; -18°C -20°C	23	4	R404a	0,84	230 V~50 Hz	720x860x2020

PROFESSIONAL CABINETS TRADITIONAL LINE

**ADN 218
ADN 219**



ADN 220



**ADN 217
ADN 226**



- AISI 304 Stainless Steel both internally and externally
- Electronic control type
- Digital display
- Automatic defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Products with solid door are tropicalised (43°C max ambient temperature)
- Products with glass door 25°C max ambient temperature
- Reversible door
- Adjustable plastic feet
- Door lock
- Internal light
- Evaporator inside the cell
- Stainless Steel grid supports
- Plastic coated grids GN 2/1

For accessories please refer to page 12

REFRIGERATORS

CODE	lt									
ADN 218	1400	1	2	-2°C +8°C	23	6	R404a	0,36	230 V~50 Hz	1440x860x2020
ADN 220	1400	1	2	+1°C +10°C	23	6	R404a	0,42	230 V~50 Hz	1440x860x2020
ADN 226	1400	2	2	+1°C +10°C	23	6	R404a	0,68	230 V~50 Hz	1440x860x2020

FREEZERS

CODE	lt									
ADN 219	1400	1	2	-18°C -20°C	23	6	R404a	1,10	230 V~50 Hz	1440x860x2020

COMBI

CODE	lt									
ADN 217	1400	1	2	+1°C +10°C -18°C -20°C	23	6	R404a	0,88	230 V~50 Hz	1440x860x2020

Accessories professional cabinets Traditional line

ADN 204		stainless steel grid GN 2/1 (to be mounted with ADN 206)
ADN 205		plastic coated grid GN 2/1 (to be mounted with ADN 206)
ADN 206		1 shelf guide
ADN 207		1 set of 4 stainless steel feet for 700 Lt
ADN 208		1 set of 5 stainless steel feet for 1400 Lt
ADN 209		1 set of 4 wheels for 700 Lt
ADN 210		1 set of 5 wheels for 1400 Lt

PROFESSIONAL CABINETS DESIGN LINE

ACO 001
ACO 002

ACO 003
ACO 004

ACO 005
ACO 006



- AISI 304 Stainless Steel both internally and externally
- Electronic control type with HACCP
- Digital display
- Automatic defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Products with solid door are tropicalised (43°C max ambient temperature)
- Products with glass door 25°C max ambient temperature
- Reversible door
- Adjustable Stainless Steel feet
- Door lock
- Internal light
- Plastic coated grid GN 2/1

For accessories please refer to page 15

REFRIGERATORS

CODE	lt									
ACO 001	700	1	1	-2°C +8°C	20	3	R404a	0,66	230V~50 Hz	720x800x2120
ACO 003	700	1	1 (glass)	-2°C +8°C	20	3	R404a	1,05	230V~50 Hz	720x800x2120
ACO 006	700	2	2	-2°C +8°C	8 + 8	4	R404a	1,04	230V~50 Hz	720x800x2120

FREEZERS

CODE	lt									
ACO 002	700	1	1	-25°C -10°C	20	3	R404a	0,72	230V~50 Hz	720x800x2120
ACO 004	700	1	1 (glass)	-25°C -10°C	20	3	R404a	1,07	230V~50 Hz	720x800x2120

COMBI

CODE	lt									
ACO 005	700	2	2	-2°C +8°C; -25°C -10°C	8 + 8	4	R404a	0,94	230V~50 Hz	720x800x2120

REFRIGERATION

ACO 007
ACO 008



ACO 011
ACO 012



- AISI 304 Stainless Steel both internally and externally
- Electronic control type with HACCP
- Digital display
- Automatic defrost
- Ventilated
- Adjustable Stainless Steel feet
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Products with solid door are tropicalised (43°C max ambient temperature)
- Products with glass door 25°C max ambient temperature
- Reversible door
- Door lock
- Internal light
- Plastic coated grid GN 2/1

ACO 009
ACO 010



ACO 013



ACO 014



For accessories please refer to page 15

REFRIGERATORS

CODE	lt									
ACO 007	1400	1	2	-2°C +8°C	20 + 20	6	R404a	1,05	230V~50 Hz	1440x800x2120
ACO 009	1400	1	2 (glass)	-2°C +8°C	20 + 20	6	R404a	0,67	230V~50 Hz	1440x800x2120
ACO 012	1400	2	2	-2°C +8°C	20 + 20	6	R404a	1,32	230V~50 Hz	1440x800x2120

FREEZERS

CODE	lt									
ACO 008	1400	1	2	-25°C -10°C	20 + 20	6	R404a	1,07	230V~50 Hz	1440x800x2120
ACO 010	1400	1	2 (glass)	-25°C -10°C	20 + 20	6	R404a	1,44	230V~50 Hz	1440x800x2120

COMBI

CODE	lt									
ACO 011	1400	2	2	-2°C +8°C; -25°C -10°C	20 + 20	6	R404a	1,38	230V~50 Hz	1440x800x2120
ACO 013	1400	4	4	-2°C +8°C; -25°C -10°C	8 + 8 + 8 + 8	8	R404a	1,90	230V~50 Hz	1440x800x2120
ACO 014	1400	3	3	700 x (-2°C +8°C) 350 x (-2°C +8°C) 350 x (-25°C -10°C)	20 + 8 + 8	7	R404a	1,60	230V~50 Hz	1440x800x2120

PROFESSIONAL CABINETS DESIGN LINE

KNOCKING DOWN SYSTEM

Whirlpool modular cabinets allow the installation of refrigeration units in areas where it would be impossible to access with standard pre-assembled cabinets. These refrigerators are assembled only once they are at the final destination.

ACO 040 - ACO 041



- AISI 304 Stainless Steel both internally and externally
- Electronic control type with HACCP
- Digital display
- Automatic defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Products with solid door are tropicalised (43°C max ambient temperature)
- Products with glass door 25°C max ambient temperature
- Reversible door
- Adjustable Stainless Steel feet
- Door lock
- Internal light
- Plastic coated grid GN 2/1

REFRIGERATORS

CODE	lt									
ACO 040	700	1	1	-2°C +8°C	20	3	R404a	0,66	230V~50 Hz	720x800x2120

FREEZERS

CODE	lt									
ACO 041	700	1	1	-25°C -10°C	20	3	R404a	0,72	230V~50 Hz	720x800x2120

Accessories professional cabinets Design line

ACO 090		1 set of 4 wheels for 700 lt
ACO 091		1 set of 5 wheels for 1400 lt
ACO 093		stainless steel grid GN 2/1 and relevant guides
ACO 094		plastic coated grid GN 2/1 and relevant guides

WITHOUT SPLASH BACK

ACO 150
ACO 153



ACO 151
ACO 154



ACO 152
ACO 155



- AISI 441 Stainless Steel both internally and externally
- Electronic control type
- Digital display
- Intelligent defrost
- Ventilated
- Automatic Water evaporation system
- R404a gas type
- HCFC and CFC free
- Tropicalised (43°C max ambient temperature)
- Reversible door
- Adjustable plastic feet
- Plastic coated grid GN 1/1
- Options available on request (to be specified at time of order):
 - tables without top (any model)
 - door locks
 - drawer modules: "1/3+2/3" or "1/3+1/3+1/3" or "1/2+1/2" in any position

For accessories please refer to page 20

REFRIGERATORS

CODE	lt									
ACO 150	280	1	2	-2°C +8°C	6+6	1 per door	R404a	0,47	230V~50 Hz	1310x700x850
ACO 151	540	1	3	-2°C +8°C	6+6+6	1 per door	R404a	0,65	230V~50 Hz	1775x700x850
ACO 152	733	1	4	-2°C +8°C	6+6+6+6	1 per door	R404a	0,88	230V~50 Hz	2240x700x850

FREEZERS

CODE	lt									
ACO 153	280	1	2	-25°C -10°C	6+6	1 per door	R404a	0,42	230V~50 Hz	1310x700x850
ACO 154	540	1	3	-25°C -10°C	6+6+6	1 per door	R404a	0,55	230V~50 Hz	1775x700x850
ACO 155	733	1	4	-25°C -10°C	6+6+6+6	1 per door	R404a	0,59	230V~50 Hz	2240x700x850

PROFESSIONAL TABLES TRADITIONAL LINE

WITH SPLASH BACK

ACO 156
ACO 159



ACO 157
ACO 160



ACO 158
ACO 161



- AISI 441 Stainless Steel both internally and externally
- Electronic control type
- Digital display
- Intelligent defrost
- Ventilated
- Automatic Water evaporation system
- R404a gas type
- HCFC and CFC free
- Tropicalised (43°C max ambient temperature)
- Reversible door
- Adjustable plastic feet
- Plastic coated grid GN 1/1
- Options available on request (to be specified at time of order):
 - tables without top (any model)
 - door locks
 - drawer modules: "1/3+2/3" or "1/3+1/3+1/3" or "1/2+1/2" in any position

For accessories please refer to page 20

REFRIGERATORS

CODE	lt									
ACO 156	280	1	2	-2°C +8°C	6+6	1 per door	R404a	0,47	230V~50 Hz	1310x700x850
ACO 157	540	1	3	-2°C +8°C	6+6+6	1 per door	R404a	0,65	230V~50 Hz	1775x700x850
ACO 158	733	1	4	-2°C +8°C	6+6+6+6	1 per door	R404a	0,88	230V~50 Hz	2240x700x850

FREEZERS

CODE	lt									
ACO 159	280	1	2	-25°C -10°C	6+6	1 per door	R404a	0,42	230V~50 Hz	1310x700x850
ACO 160	540	1	3	-25°C -10°C	6+6+6	1 per door	R404a	0,55	230V~50 Hz	1775x700x850
ACO 161	733	1	4	-25°C -10°C	6+6+6+6	1 per door	R404a	0,59	230V~50 Hz	2240x700x850

WITHOUT SPLASH BACK

ACO 100
ACO 104



ACO 101
ACO 105



ACO 102
ACO 106



ACO 103
ACO 107



- AISI 304 Stainless Steel both internally and externally
- Electronic control type with HACCP
- Digital display
- Intelligent defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Tropicalised (43°C max ambient temperature)
- Reversible door
- Self closing door
- Adjustable Stainless Steel feet
- Plastic coated grid GN 1/1
- Options available on request (to be specified at time of order):
 - tables without top (any model)
 - door locks
 - drawer modules: "1/3+2/3" or "1/3+1/3+1/3" or "1/2+1/2" in any position

For accessories please refer to page 20

REFRIGERATORS

CODE	lt									
ACO 100	120	1	1	-2°C +8°C	6	1 per door	R404a	0,18	230 V~50 Hz	970x700x850
ACO 101	280	1	2	-2°C +8°C	6+6	1 per door	R404a	0,48	230 V~50 Hz	1460x700x850
ACO 102	540	1	3	-2°C +8°C	6+6+6	1 per door	R404a	0,65	230 V~50 Hz	1945x700x850
ACO 103	733	1	4	-2°C +8°C	6+6+6+6	1 per door	R404a	0,88	230 V~50 Hz	2430x700x850

FREEZERS

CODE	lt									
ACO 104	120	1	1	-25°C -10°C	6	1 per door	R404a	0,16	230 V~50 Hz	970x700x850
ACO 105	280	1	2	-25°C -10°C	6+6	1 per door	R404a	0,42	230 V~50 Hz	1460x700x850
ACO 106	540	1	3	-25°C -10°C	6+6+6	1 per door	R404a	0,55	230 V~50 Hz	1945x700x850
ACO 107	733	1	4	-25°C -10°C	6+6+6+6	1 per door	R404a	0,59	230 V~50 Hz	2430x700x850

PROFESSIONAL TABLES DESIGN LINE

WITH SPLASH BACK

ACO 108
ACO 112



ACO 109
ACO 113



ACO 110
ACO 114



ACO 111
ACO 115



- AISI 304 Stainless Steel both internally and externally
- Electronic control type with HACCP
- Digital display
- Intelligent defrost
- Ventilated
- Automatic water evaporation system
- R404a gas type
- HCFC and CFC free
- Tropicalised (43°C max ambient temperature)
- Reversible door
- Self closing door
- Adjustable Stainless Steel feet
- Plastic coated grid GN 1/1
- Options available on request (to be specified at time of order):
 - tables without top (any model)
 - door locks
 - drawer modules: "1/3+2/3" or "1/3+1/3+1/3" or "1/2+1/2" in any position

For accessories please refer to page 20





REFRIGERATORS

CODE	lt									
ACO 108	120	1	1	-2°C +8°C	6	1 per door	R404a	0,18	230V~50 Hz	970x700x850
ACO 109	280	1	2	-2°C +8°C	6+6	1 per door	R404a	0,78	230V~50 Hz	1460x700x850
ACO 110	540	1	3	-2°C +8°C	6+6+6	1 per door	R404a	0,65	230V~50 Hz	1945x700x850
ACO 111	733	1	4	-2°C +8°C	6+6+6+6	1 per door	R404a	0,88	230V~50 Hz	2430x700x850

FREEZERS

CODE	lt									
ACO 112	120	1	1	-25°C -10°C	6	1 per door	R404a	0,16	230V~50 Hz	970x700x850
ACO 113	280	1	2	-25°C -10°C	6+6	1 per door	R404a	0,42	230V~50 Hz	1460x700x850
ACO 114	540	1	3	-25°C -10°C	6+6+6	1 per door	R404a	0,55	230V~50 Hz	1945x700x850
ACO 115	733	1	4	-25°C -10°C	6+6+6+6	1 per door	R404a	0,59	230V~50 Hz	2430x700x850

Accessories
Professional tables
Traditional and
Design line







ACO 090		1 set of 4 wheels 1- or 2-door tables
ACO 091		1 set of 5 wheels 3-door tables
ACO 092		1 set of 6 wheels 4-door tables
ACO 097		plastic-coated GN 1/1 grid and guides

ICE MAKERS TRADITIONAL LINE

AGB 022 - AGB 024









- AISI 304 Stainless Steel both internally and externally
- Cube ice shape
- Air condensed
- Static evaporator
- Hot gas defroster
- Roll bond system








CODE		 Kg	Ice shape	Condenser type	System				
AGB 022	24	10	cube	air	Roll bond	R134a	0,21	230 V~50-60Hz	555x535x590
AGB 024	40	20	cube	air	Roll bond	R134a	0,34	230 V~50-60Hz	556x535x850

ICE CUBE MAKERS




- AISI 304 Stainless Steel both internally and externally
- Ice in cube, fingers or flakes
- Air condensed
- Static evaporator
- Hot gas defroster

CODE		 Kg	Ice shape	Condenser type	System		 kW	 V	
ADN 108	20	6	cube	air	spray	R404a	0,36	230V~50-60Hz	350x474x592
ADN 110	30	12	cube	air	spray	R404a	0,43	230V~50-60Hz	405x515x750
ADN 112	45	20	cube	air	spray	R404a	0,54	230V~50-60Hz	465x595x795
ADN 114	60	25	cube	air	spray	R404a	0,65	230V~50-60Hz	535x595x795
ADN 116	80	35	cube	air	spray	R404a	0,78	230V~50-60Hz	715x595x945
ADN 118	150	75	cube	air	spray	R404a	1,35	230V~50-60Hz	860x700x1050
ADN 120	153	(storage bin AGS 852/WP)	cube	air	spray	R404a	1,5	230V~50-60Hz	775x625x805







ADN 108	
ADN 110	
ADN 112	
ADN 114	
ADN 116	
ADN 118	
ADN 120	

ICE MAKERS DESIGN LINE

ICE FINGER MAKERS









- AISI 304 Stainless Steel both internally and externally
- Ice in cube, fingers or flakes
- Air condensed
- Static evaporator
- Hot gas defroster

CODE		 Kg	Ice shape	Condenser type	System		 kW	 V	
AGS 836/WP	20	9	fingers	air	paddle	R404a	0,33	230 V~50-60Hz	405x510x770
AGS 838/WP	30	12	fingers	air	paddle	R404a	0,33	230 V~50-60Hz	405x510x825
AGS 840/WP	40	18	fingers	air	paddle	R404a	0,36	230 V~50-60Hz	405x510x950
AGS 842/WP	50	20	fingers	air	paddle	R404a	0,43	230 V~50-60Hz	515x555x950
AGS 844/WP	60	30	fingers	air	paddle	R404a	0,43	230 V~50-60Hz	555x595x1075
AGS 846/WP	90	37	fingers	air	paddle	R404a	0,65	230 V~50-60Hz	675x555x1075
AGS 848/WP	130	50	fingers	air	paddle	R404a	0,78	230 V~50-60Hz	845x555x1075
ADN 106	150	100	fingers	air	paddle	R404a	0,80	230 V~50-60Hz	840x700x1150
AGS 850/WP	180	(storage bin AGS 852/WP)	fingers	air	paddle	R404a	1,60	230 V~50-60Hz	690x565x1125

ICE FLAKE MAKERS



- AISI 304 Stainless Steel both internally and externally
- Ice in cube, fingers or flakes
- Air condensed



CODE		 Kg	Ice shape	Condenser type	System				
ADN 100	45	14	flakes	air	-	R134a	0,46	230 V~50-60Hz	405x515x750
ADN 102	85	20	flakes	air	-	R404a	0,53	230 V~50-60Hz	465x595x795
AGS 834/WP	135	60	flakes	air	-	R404a	0,64	230 V~50-60Hz	515x550x1435
ADN 104	220	(storage bin AGS 852/WP)	flakes	air	-	R404a	0,95	230 V~50-60Hz	515x550x575

AGS 852/WP



- Guarantees an abundant stock of ice: 200 kg
- 18/8 stainless steel housing

AGS 852/WP storage bin model works with all 200 Kg/24h Ice Makers from Whirlpool range: AGS 850/WP, ADN 120, ADN 104

	
760x800x1030	200 Kg

SHOCK FREEZER

ACO 080



- AISI 304 Stainless Steel
- 3 levels GN 1/1 but also GN 2/3, GN 1/2, and GN 1/3
- Left-hand hinges
- Condensing unit included
- Electronic control type
- Digital display
- R404a gas type
- HCFC and CFC free
- Manual defrost cycle
- Automatic cycle with core probe
- 70 mm distance between levels

CODE				 +70°C -18°C 270 min	 +70°C +3°C 90 min		 kW	 V	
ACO 080	3	GN 1/1	1	8 kg	12 kg	R404a	0,65	230V~50 Hz	620x650x650

ACO 081



ACO 082



- AISI 304 Stainless Steel
- Right-hand hinges
- Condensing unit included
- Electronic control with touch system
- Digital display
- R404a gas type
- HCFC and CFC free
- Manual defrost cycle for ACO 081
- Electric defrost for ACO 082 and ACO 083
- Automatic cycle with core probe
- UV disinfection for ACO 082 and ACO 083
- 70 mm distance between levels

ACO 083



For accessories please refer to page 26

CODE				 +70°C -18°C 270 min	 +70°C +3°C 90 min		 kW	 V	
ACO 081	5	GN 1/1 and 600x400 mm	1	9 kg	13 kg	R404a	0,65	230V~50 Hz	830x800x830
ACO 082	6	GN 1/1 and 600x400 mm	1	12 kg	18 kg	R404a	0,87	230V~50 Hz	820x825x1400
ACO 083	10	GN 1/1 and 600x400 mm	1	18 kg	28 kg	R404a	1,13	230V~50 Hz	820x825x1680

ACO 084

ACO 085



- AISI 304 Stainless Steel
- Roll-in version
- Right door hinges
- Condensing unit not included
- Electronic control with touch system
- Digital display
- R404a gas type
- HCFC and CFC free
- Manual defrost cycle
- Automatic cycle with core probe
- UV disinfection
- 66 mm distance between levels

CODE				 +70°C -18°C 270 min	 +70°C +3°C 90 min	 kW	 V	
ACO 084	20	GN 1/1 and 600x400 mm	1	36 kg	56 kg	0,9	400 V tri ~ 50 Hz	1100x1100x2150
ACO 085	40	GN 1/1 and 600x400 mm	1	72 kg	112 kg	1,2	400 V tri ~ 50 Hz	1500x1300x2150

	CODE		 kW	 V	
Remote Cold Unit Air Condenser 3,0 Hp for ACO 084	ACO 086	R404A	4,24	400 V tri ~ 50 Hz	1150x700x660
Remote Cold Unit Air Condenser 5,0 Hp for ACO 085	ACO 087	R404A	5,78	400 V tri ~ 50 Hz	1150x750x800

Option Shock Freezer (to be specified at the time of order):

- HACCP printer on board (excluded ACO 080)
- left opening door (excluded ACO 080, ACO 084 and ACO 085)
- U.V. lamp (excluded ACO 080 and ACO 081)

Accessories Shock Freezer

ACO 180		Stand for ACO 080
ACO 181		4 wheels kit (2 with brakes) for ACO 081, ACO 082, ACO 083
ACO 182		4 adjustable Stainless Steel feet for ACO 081

NOTE

A series of horizontal dotted lines for writing notes.

Whirlpool Europe s.r.l.
V.le Guido Borghi, 27
21025 - Comerio - (VA) ITALY
www.whirlpool-professional.com



SENSING THE DIFFERENCE

Specifications and technical information are subject to change at any time.

While every effort has been made to ensure that the information contained in this brochure is correct at time of going to press.

Whirlpool can not be held responsible for any errors or omissions that may come to light after publication.

Products offered for sale may differ from those described or illustrated here and Whirlpool reserve the right to alter specifications without prior notice.

Due to printing limitations the colour of appliances illustrated herein cannot be guaranteed accurate, and should be used for guidance only.

If particular features, colours or measurements as important to you please check with your Whirlpool dealer before purchase.