

WHIRLPOOL

COMMERCIAL REFRIGERATORS

ACO 050

ACO 051

ACO 052

ACO 053

376 lt

325 lt



■ up to 65% energy savings

- Certified for commercial use
 - High efficiency compressor
 - Low noise level
 - Soft opening system with granted patent
 - Electronic control type with 6th Sense Technology
 - Digital display
 - Intelligent defrost
 - Ventilated
 - New antibacterial filter*
 - Automatic Water Evaporation System
 - R600a gas type
 - HCFC and CFC free
 - Robust handle
 - Pigeon pair with the freezer
 - Reversible door
 - Feet adjustable
 - Perfect for kiosks, pubs, small restaurants, B&Bs
 - Best price quality
- * Code antibacterial filter: ANTF-MIC 481248048172

Commercial code	ACO 050	ACO 051	ACO 052	ACO 053
12NC	850605001000	850605101000	850605201000	850605301000
Colour	White	Silver	White	Silver
Capacity (LT)	376	376	325	325
Cells temperature	+3°C +8°C	+3°C +8°C	+3°C +8°C	+3°C +8°C
Power (W)	150	150	150	150
Volt	230V 50Hz 1+N	230V 50Hz 1+N	230V 50Hz 1+N	230V 50Hz 1+N
Plug type	Shuko	Shuko	Shuko	Shuko
Ambient Working Class	+10°C +30°C	+10°C +30°C	+10°C +30°C	+10°C +30°C
Grids supports nr	6	6	5	5
Grids included nr	7	7	6	6
Grids material	Plastic Coated	Plastic Coated	Plastic Coated	Plastic Coated
Internal light	Yes	Yes	Yes	Yes
Product Dimensions wxdxh(mm)	1790x596x625	1790x596x625	1590x596x625	1590x596x625
Product packaged weight (kg)	66	66	46	46

www.whirlpool-professional.com



COMMERCIAL FREEZERS

ACO 054

WITH DRAWERS

ACO 055

WITHOUT DRAWERS

ACO 056

WITH DRAWERS

ACO 057

WITHOUT DRAWERS

266 lt

232 lt



■ up to 65% energy savings

- Certified for commercial use
- High efficiency compressor
- Low noise level
- Soft opening system with granted patent
- Electronic control type with 6th Sense Technology
- Digital display
- R600a gas type
- HCFC and CFC free
- Robust handle
- Pigeon pair with the refrigerators
- Reversible door
- Feet adjustable
- Perfect for kiosks, pubs, small restaurants, B&Bs
- Best price quality

Commercial code	ACO 054	ACO 055	ACO 056	ACO 057
12NC	850605401000	850605501000	850605601000	850605701000
Colour	White	White	White	White
Capacity (LT)	266	266	232	232
Cells temperature	-25°C -18°C	-25°C -18°C	-25°C -18°C	-25°C -18°C
Power (W)	100	100	80	80
Volt	230V 50Hz 1+N	230V 50Hz 1+N	230V 50Hz 1+N	230V 50Hz 1+N
Plug type	Shuko	Shuko	Shuko	Shuko
Ambient Working Class	+10°C +43°C	+10°C +43°C	+10°C +43°C	+10°C +43°C
Grids	6 shelved static evaporator	6 shelved static evaporator	5 shelved static evaporator	5 shelved static evaporator
Internal light	No	No	No	No
Product Dimensions wxdxh(mm)	1790x596x625	1790x596x625	1590x596x625	1590x596x625
Product packaged weight (kg)	67	67	47	47

